

View Online at <https://aerobasegroup.com/nsn/5925-00-261-7702>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Length:**

1.100 inches

**Body Width:**

2.350 inches

**Body Height:**

1.350 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.704 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.780 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

1.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

145.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.469 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

160.0 degrees fahrenheit all locations

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0