NSN 5925-00-264-5649

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-264-5649

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

1.300 inches

Body Width:

2.063 inches

Body Height:

1.875 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

Center To Center Distance Between Terminals Parallel To Width:

0.688 inches

- **Pole Quantity:**
- 3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

1.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

NSN 5925-00-264-5649

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 0.350 at 200 pct all locations and 4.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Shock resistant and vibration resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations **Frequency In Hertz:** 400.0 all locations **Unpackaged Unit Weight:** 154.0 grams **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Uns **Terminal Type And Quantity:** 6 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0