

View Online at <https://aerobasegroup.com/nsn/5925-00-264-6251>

Body Style:

Multipole-multiple actuator type

Body Length:

2.490 inches

Body Width:

1.530 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.475 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Ultimate Trip Time Per Pole In Seconds:

6.000 and 60.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

3.5 millimeters

Thread Pitch In Millimeters:

Any acceptable

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 150 pct and 60.000 at 150 pct and 0.400 at 400 pct and 1.500 at 400 pct all locations

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

10.0 ac

Switch Voltage Rating And Type In Volts:

250.0 ac

Thread Tolerance Class:

Any acceptable

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

7.400 ounces

Thread Series Designator:

Iso s

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0