

View Online at <https://aerobasegroup.com/nsn/5925-00-265-2275>

**Body Style:**

Multipole-single actuator type

**Body Length:**

5.250 inches

**Body Width:**

3.000 inches

**Body Height:**

2.687 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

4.359 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.984 inches

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.063 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.984 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.218 inches

**Mounting Surface To Terminal End Distance:**

Between 3.177 inches and 3.197 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole and 4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.164 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.320 at 200 pct all locations and 0.950 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose and fungus resistant and moisture resistant

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

29.000 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0