

View Online at <https://aerobasegroup.com/nsn/5925-00-267-1459>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.190 inches

**Overall Height:**

2.850 inches

**Overall Width:**

1.515 inches

**Case Material:**

Metal

**Switch Contact Arrangement:**

Single pole, double throw

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

29.0 dc first location

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip w/dual rating and remote trip feature first location

**Thread Size:**

0.138 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Switch Location And Position Designation:**

Internal at pole one

**Reset Actuator Voltage Rating And Type In Volts:**

29.0 dc

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 200 pct all locations and 9.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

1.0 dc

**Switch Voltage Rating And Type In Volts:**

28.0 dc

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab, solder lug and 6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A030a0