

View Online at <https://aerobasegroup.com/nsn/5925-00-270-5986>

Body Style:

Rectangular dimensional envelope

Overall Length:

4.750 inches

Overall Height:

3.250 inches

Overall Width:

3.750 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac all locations and 175.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

122.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+500.0/+1750.0 ac all locations and +500.0/+1750.0 dc all locations

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

108.000 at 200 pct all locations and 500.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0