

View Online at <https://aerobasegroup.com/nsn/5925-00-271-8836>

Overall Length:

6.000 inches

Overall Height:

3.969 inches

Overall Width:

1.375 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

1

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

120.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Trip Delay Time In Seconds Per Rated Continuous Current:

2600.000 at 125 pct single location and 75.000 at 200 pct single location and 24.000 at 300 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Special Features:

Mtg holes diagonally spaced 0.812 by 4.844 in c to c

Frequency In Hertz:

60.0 single location

Precious Material:

Silver

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0