NSN 5925-00-272-7002

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-272-7002

Body Style: Single pole type Overall Length: 3.156 inches Body Width: 1.875 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Overall Length: 3.156 inches Body Width: 1.875 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
3.156 inches Body Width: 1.875 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
Body Width: 1.875 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
1.875 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
Plastic Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
Center To Center Distance Between Terminals Parallel To Length: 1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
1.062 inches Unthreaded Mounting Hole Diameter: 0.250 inches
Unthreaded Mounting Hole Diameter: 0.250 inches
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.406 inches
Mounting Surface To Terminal End Distance:
1.640 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
105.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
575.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button

NSN 5925-00-272-7002

Circuit Breaker - Page 2 of 2



Actuator Function: Reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Trip Delay Time In Seconds Per Rated Continuous Current: 15.000 at 200 pct single location and 50.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Dustproof and weatherproof **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Terminal Type And Quantity:** 2 threaded stud Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0