

View Online at <https://aerobasegroup.com/nsn/5925-00-279-1035>

Body Style:

Single pole type

Body Length:

3.719 inches

Body Width:

0.990 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.063 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.156 inches

Mounting Surface To Terminal End Distance:

3.239 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.500 at 200 pct single location and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Explosion resistant

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0