## NSN 5925-00-279-1331



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-279-1331 **Body Style:** Single pole type **Body Length:** 3.750 inches **Body Width:** 0.969 inches **Body Height:** 2.250 inches **Case Material:** Metal **Fragility Factor:** Moderately rugged **Boss Height:** 0.109 inches

,

**Arc Quenching Method:** 

Air

**Mounting Facility Type And Quantity:** 

1 slot

Storage Type:

**Pole Quantity:** 

Any acceptable

**Cubic Measure:** 

8.176 cubic inches

**Maximum Continuous Load Current Rating Per Pole:** 

15.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:** 

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

**Circuit Protection Type:** 

Overcurrent single location

**Trip Release Method:** 

Thermal-magnetic single location

**Trip Release Characteristic:** 

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

120.0 single location

**Reset Method:** 

Manual

**Main Contact Tripping Mechanism Type:** 

Trip free

## NSN 5925-00-279-1331

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
24.000 at 200 pct single location and 58.000 at 200 pct single location
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0