NSN 5925-00-279-2924

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-279-2924

Body Style:
Single pole type
Overall Length:
2.000 inches
Body Width:
1.188 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.574 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.266 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
35.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
600.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:

Series trip single location

NSN 5925-00-279-2924

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct single location and 60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Corrosion resistant and dustproof and shockproof and vibrationproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Unpackaged Unit Weight:

1.500 ounces

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0