## NSN 5925-00-279-2925

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-279-2925

Body Style:
Single pole type
Overall Length:
2.000 inches
Body Width:
1.250 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.574 inches
Mounting Surface To Terminal End Distance:
1.266 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
35.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
600.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
130.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button

## NSN 5925-00-279-2925

Circuit Breaker - Page 2 of 2



Actuator Function:	
Trip-reset	
Actuator Position Designation:	
At pole one	
Internal Trip Release Configuration:	
Series trip single location	
Trip Delay Time In Seconds Per Rated Continuous Current:	
30.000 at 200 pct single location	
Inclosure Protection Type For Which Designed:	
Weatherproof	
Trip Release Ambient Tempurature Rating:	
25.0 degrees celsius single location	
Terminal Type And Quantity:	
2 tab w/screw	
Shelf Life:	
N/a	
Unit Of Measure:	
<del>.</del>	
Demilitarization:	
No	
Fiig:	
A030a0	