## NSN 5925-00-279-5601



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-279-5601 **Body Style:** Rectangular dimensional envelope **Overall Length:** 4.750 inches **Overall Height:** 3.250 inches **Overall Width:** 3.870 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 200.0 amperes ac all locations and 200.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 122.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +600.0/+2000.0 ac all locations and +600.0/+2000.0 dc all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 108.000 at 200 pct all locations and 500.000 at 200 pct all locations **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 4 compression Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5925-00-279-5601

Circuit Breaker Tripper - Page 2 of 2



Fiig:

A030a0