# NSN 5925-00-279-5604

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-279-5604

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

7.750 inches

## **Overall Height:**

4.500 inches

#### **Overall Width:**

5.250 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

#### Circuit Protection Type:

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

123.0 all locations

#### Manual Actuator Type And Quantity:

1 toggle

#### **Actuator Function:**

Trip-reset

#### Actuator Position Designation:

At pole two

#### Trip Delay Time In Seconds Per Rated Continuous Current:

132.000 at 200 pct all locations and 650.000 at 200 pct all locations

#### Trip Release Ambient Tempurature Rating:

25.0 degrees celsius all locations

#### **Frequency In Hertz:**

60.0 all locations

## **Terminal Type And Quantity:**

6 compression

#### Shelf Life:

N/a

# NSN 5925-00-279-5604

Circuit Breaker Tripper - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0

