

View Online at <https://aerobasegroup.com/nsn/5925-00-279-6742>

Pole Quantity:

2

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 dc all locations

Circuit Protection Type:

Overcurrent second location

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull and 1 rotary

Actuator Function:

Trip w/separate reset

Auxiliary Switch Function And Quantity:

1 control

Adjustable Trip Setting Current Range Per Pole In Amps:

+200.0/+400.0 dc all locations

Terminal Type And Quantity:

4 bus bar

Reference Number Differentiating Characteristics:

As differentiated by pole quantity; continuous load current rating per pole; operating voltage type and rating per pole in volts; adjustable trip setting current range per pole in amps

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0