

View Online at <https://aerobasegroup.com/nsn/5925-00-279-6742>

**Pole Quantity:**

2

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

200.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

25000.0 dc all locations

**Circuit Protection Type:**

Overcurrent second location

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull and 1 rotary

**Actuator Function:**

Trip w/separate reset

**Auxiliary Switch Function And Quantity:**

1 control

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+200.0/+400.0 dc all locations

**Terminal Type And Quantity:**

4 bus bar

**Reference Number Differentiating Characteristics:**

As differentiated by pole quantity; continuous load current rating per pole; operating voltage type and rating per pole in volts; adjustable trip setting current range per pole in amps

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0