

View Online at <https://aerobasegroup.com/nsn/5925-00-279-6757>

**Overall Length:**

4.125 inches

**Overall Height:**

4.125 inches

**Overall Width:**

3.344 inches

**Case Material:**

Plastic

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations and 50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations and 120.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations and 5000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 100.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Shockproof and vibrationproof

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 quick disconnect, male

**Specification Or Standard:**

Alb-5 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0