

View Online at <https://aerobasegroup.com/nsn/5925-00-283-6511>

Body Style:

Single pole type

Overall Length:

2.000 inches

Body Width:

1.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.969 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.625 inches

Mounting Surface To Terminal End Distance:

1.375 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

600.0 ac single location and 600.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

11.000 at 200 pct single location and 190.000 at 200 pct single location

Incllosure Protection Type For Which Designed:

Weatherproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0