## NSN 5925-00-283-6511

Circuit Breaker - Page 1 of 2

Body Style: Single pole type Overall Length: 2.000 inches



View Online at https://aerobasegroup.com/nsn/5925-00-283-6511

Body Width:
1.250 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.969 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.625 inches
Mounting Surface To Terminal End Distance:
1.375 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
25.0 amperes ac single location and 25.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 ac single location and 30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
600.0 ac single location and 600.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:

11.000 at 200 pct single location and 190.000 at 200 pct single location

## NSN 5925-00-283-6511

Circuit Breaker - Page 2 of 2



## Inclosure Protection Type For Which Designed: Weatherproof Trip Release Ambient Tempurature Rating: 25.0 degrees celsius single location Frequency In Hertz: 60.0 single location Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A030a0