## NSN 5925-00-283-6516

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-283-6516

De de Otdes
Body Style:
Single pole type
Body Length:
3.750 inches
Body Width:
0.969 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
2.624 inches
Unthreaded Mounting Hole Diameter:
0.209 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.624 inches
Mounting Surface To Terminal End Distance:
2.547 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
10.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
125.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
120.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle

## NSN 5925-00-283-6516

Circuit Breaker - Page 2 of 2



**Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Trip Delay Time In Seconds Per Rated Continuous Current: 48.000 at 200 pct single location and 13.000 at 300 pct single location **Inclosure Protection Type For Which Designed:** General purpose **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Frequency In Hertz:** 60.0 single location **Terminal Type And Quantity:** 2 screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0