

View Online at <https://aerobasegroup.com/nsn/5925-00-283-7979>

Body Length:

5.250 inches

Body Width:

2.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.359 inches

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Boss Height:

0.219 inches

Mounting Surface To Terminal End Distance:

3.313 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

230.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.500 at 200 pct all locations and 19.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

1.250 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0