

View Online at <https://aerobasegroup.com/nsn/5925-00-283-8139>

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.438 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

75.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

355.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1400.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Auxiliary Switch Function And Quantity:

1 control

Terminal Type And Quantity:

6 threaded stud

Reference Number Differentiating Characteristics:

As differentiated by pole quantity, maximum continuous load current rating, operating voltage type and rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0