NSN 5925-00-284-3233

Circuit Breaker - Page 1 of 2

Body Style:Single pole type



View Online at https://aerobasegroup.com/nsn/5925-00-284-3233

Overall Length:
2.000 inches
Body Width:
1.188 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.975 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.574 inches
Mounting Surface To Terminal End Distance:
1.288 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac single location and 30.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
220.0 ac single location and 30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac single location and 300.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:

3.750 at 200 pct single location and 10.000 at 200 pct single location

NSN 5925-00-284-3233

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed: Fungus resistant Trip Release Ambient Tempurature Rating: 25.0 degrees celsius single location Frequency In Hertz: 400.0 single location Unpackaged Unit Weight: 1.500 ounces Terminal Type And Quantity: 2 tab w/screw Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A030a0