NSN 5925-00-284-3726

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-284-3726

| Body Style: |
|--|
| Rectangular dimensional envelope |
| Overall Length: |
| 8.341 inches |
| Overall Height: |
| 4.250 inches |
| Overall Width: |
| 4.625 inches |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 3 |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 6 terminal |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Adjustable trip release |
| Maximum Continuous Load Current Rating Per Pole: |
| 125.0 amperes ac all locations and 125.0 amperes dc all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 500.0 ac all locations and 250.0 dc all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Thermal-magnetic all locations |
| Trip Release Characteristic: |
| Instantaneous all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 150.0 all locations |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole two |
| Adjustable Trip Setting Current Range Per Pole In Amps: |
| +650 0/+1300 0 ac all locations and +650 0/+1300 0 dc all locations |

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-284-3726Circuit Breaker Tripper - Page 2 of 2



| Frequency In Hertz: |
|---------------------------------|
| 60.0 all locations |
| Unpackaged Unit Weight: |
| 4.000 pounds |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 6 tab w/screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A030a0