

View Online at <https://aerobasegroup.com/nsn/5925-00-308-2712>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.000 inches

**Body Width:**

3.000 inches

**Body Height:**

3.062 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Any acceptable

**Center To Center Distance Between Terminals Parallel To Width:**

0.828 inches

**Unthreaded Mounting Hole Diameter:**

0.161 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Any acceptable

**Boss Height:**

Any acceptable

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

70.000 and 200.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0