NSN 5925-00-318-2222

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-318-2222

Body Length:
8.000 inches
Body Width:
4.500 inches
Body Height:
3.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Boss Height:
0.156 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 terminal
Maximum Continuous Load Current Rating Per Pole:
100.0 amperes ac all locations and 100.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations and 250.000 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
2000.0 ac all locations and 10000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:

150.000 at 200 pct all locations and 250.000 at 200 pct all locations

NSN 5925-00-318-2222

Circuit Breaker - Page 2 of 2



Trip Release Ambie	nt Tempurature Rating
40.0 degrees celsius	all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 clip and 3 compression

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0