

View Online at <https://aerobasegroup.com/nsn/5925-00-329-5655>

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

0.750 inches

Body Width:

1.750 inches

Body Height:

1.350 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

Center To Center Distance Between Terminals Parallel To Width:

0.599 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct all locations and 40.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

250.0 degrees fahrenheit all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0