NSN 5925-00-333-1584

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-333-1584 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 1.813 inches **Body Height:** 1.875 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.174 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.566 inches and 1.582 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 575.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Reset Method:**

Automatic

Internal Trip Release Configuration:

Series trip single location

NSN 5925-00-333-1584

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Waterproof and vibration resistant and shock resistant and salt spray proof and fungus resistant

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Test Data Document:

81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 quick disconnect, female

Specification Data:

81349--13516/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0