

View Online at <https://aerobasegroup.com/nsn/5925-00-335-8727>

**Body Style:**

Single pole type

**Overall Length:**

1.969 inches

**Overall Width:**

0.719 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.536 inches

**Boss Height:**

0.125 inches

**Mounting Surface To Terminal End Distance:**

2.157 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes ac single location and 500.0 milliamperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 24.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5.0 ac single location and 5.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct single location and 40.000 at 200 pct single location

**Trip Release Ambient Temperature Rating:**

68.0 degrees fahrenheit single location

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0