NSN 5925-00-348-3591

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-348-3591

Body Style:

Single pole type

Bushing Length:

Between 0.219 inches and 0.281 inches

Body Length:

Between 0.719 inches and 0.781 inches

Body Width:

Between 0.531 inches and 0.593 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.672 inches and 0.734 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.919 inches and 1.981 inches

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac single location and 7.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

Reset Method:

Manual

NSN 5925-00-348-3591

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location and 20.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Vibrationproof and fungus resistant and moisture resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Frequency In Hertz:** 400.0 single location **Unpackaged Unit Weight:** 38.0 grams **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0