## NSN 5925-00-350-4369

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-350-4369

View Online at https://aerobasegroup.com/nsn/5925-00-350-4369
Body Style:
Single pole type
Overall Length:
2.188 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.781 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.812 inches
Mounting Surface To Terminal End Distance:
1.297 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
25.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
2000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
130.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Reset

## NSN 5925-00-350-4369

Circuit Breaker - Page 2 of 2



**Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location **Thread Size:** 0.164 inches Trip Delay Time In Seconds Per Rated Continuous Current: 8.000 at 200 pct single location and 50.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Dustproof and fungus resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Test Data Document:** 81349-mil-c-13516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc **Terminal Type And Quantity:** 2 screw Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0