

View Online at <https://aerobasegroup.com/nsn/5925-00-350-4481>

Overall Length:

2.000 inches

Overall Height:

1.266 inches

Overall Width:

1.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.187 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

15.0 ac single location and 15.0 dc single location and 30.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

900.0 ac single location and 900.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 125 pct single location and 30.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and dustproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Specification Or Standard:

2 type and b grade and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0