# NSN 5925-00-356-7742

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-356-7742

## Body Style:

Single pole type

## **Bushing Length:**

0.250 inches

## **Body Length:**

0.781 inches

#### **Body Width:**

0.593 inches

#### **Case Material:**

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

## Mounting Surface To Terminal End Distance:

1.343 inches

#### **Pole Quantity:**

1

#### Mounting Facility Type And Quantity:

1 threaded bushing

#### Storage Type:

General purpose warehouse

## Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac single location

## **Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2800.0 ac single location

## **Circuit Protection Type:**

Overcurrent single location

#### **Trip Release Method:**

Thermal single location

#### **Trip Release Characteristic:**

Time delay single location

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

## Manual Actuator Type And Quantity:

1 push-pull

NSN 5925-00-356-7742

Circuit Breaker - Page 2 of 2



Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

## Thread Size:

0.437 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

1.500 at 200 pct single location and 30.000 at 200 pct single location

**Trip Release Ambient Tempurature Rating:** 

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

#### **Test Data Document:**

81349-mil-c-5809 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Thread Series Designator:

Uns

Terminal Type And Quantity: 2 screw Specification Data: 96906-ms3320 government standard Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No

Fiig:

A030a0