NSN 5925-00-359-4001

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-359-4001

Thread Pitch Diameters:

+0.3503/+0.3537 inches

Body Style:

Multipole-single actuator type

Bushing Length:

0.375 inches

Body Length:

1.562 inches

Body Width:

1.937 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.828 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc third location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations and 500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

NSN 5925-00-359-4001

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two **Auxiliary Switch Function And Quantity:** 3 alarm Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.375 inches **Switch Location And Position Designation:** Internal at each pole Trip Delay Time In Seconds Per Rated Continuous Current: 0.007 at 150 pct all locations and 0.030 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Hermetically sealed Switch Terminal Type: Tab, solder lug Switch Current Rating And Type In Amps: 0.5 dc Switch Voltage Rating And Type In Volts: 50.0 dc **Frequency In Hertz:** 60.0 all locations **Thread Series Designator:** Unef **Terminal Type And Quantity:** 6 wire hook Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0