

View Online at <https://aerobasegroup.com/nsn/5925-00-395-3566>

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

2

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

8 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

3000.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

60000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Auxiliary Switch Function And Quantity:

1 control

Adjustable Trip Setting Current Range Per Pole In Amps:

+3000.0/+6000.0 dc all locations

Terminal Type And Quantity:

4 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0