# NSN 5925-00-396-2283

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-396-2283

Overall	Length:
Overall	Lengui.

10.000 inches

#### **Overall Height:**

4.750 inches

# **Overall Width:**

5.000 inches

#### **Case Material:**

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.281 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 8.750 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.625 inches

#### **Pole Quantity:**

2

## Arc Quenching Method:

Deion

# Mounting Facility Type And Quantity:

4 unthreaded hole

#### Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

# Manual Actuator Type And Quantity:

1 toggle

# Actuator Function:

Reset

# NSN 5925-00-396-2283

Circuit Breaker - Page 2 of 2



### Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

# Frequency In Hertz:

60.0 all locations

# Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A030a0