

View Online at <https://aerobasegroup.com/nsn/5925-00-396-2303>

**Overall Length:**

10.000 inches

**Overall Height:**

4.750 inches

**Overall Width:**

5.000 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

8.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.625 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

200.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 240.000 at 200 pct all locations and 2.000 at 300 pct all locations and 7.500 at 300 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0