## NSN 5925-00-396-2311

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-396-2311 **Overall Length:** 10.000 inches **Overall Height:** 4.750 inches **Overall Width:** 5.000 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.281 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 8.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.625 inches **Pole Quantity: Arc Quenching Method:** Deion **Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Reset

**Actuator Function:** 

## NSN 5925-00-396-2311

Circuit Breaker - Page 2 of 2



## Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 240.000 at 200 pct all locations and 2.000 at 200 pct all locations and 7.500 at 300 pct all locations

**Trip Release Ambient Tempurature Rating:** 

50.0 degrees celsius all locations

**Terminal Type And Quantity:** 

4 threaded stud

Shelf Life:

•...•.. <u>-</u>.

**Unit Of Measure:** 

--

N/a

Demilitarization:

No

Fiig:

A030a0