

View Online at <https://aerobasegroup.com/nsn/5925-00-396-2311>

Overall Length:

10.000 inches

Overall Height:

4.750 inches

Overall Width:

5.000 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.625 inches

Pole Quantity:

2

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 240.000 at 200 pct all locations and 2.000 at 200 pct all locations and 7.500 at 300 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0