## NSN 5925-00-399-5983



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-399-5983 **Overall Length:** 2.188 inches **Overall Height:** 2.688 inches Overall Width: 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.813 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 115.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1200.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 push-pull **Actuator Function:** 

Reset

**Thread Size:** 

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 100.000 at 200 pct single location

## NSN 5925-00-399-5983

Circuit Breaker - Page 2 of 2



| Trip Release Ambient Tempurature Rating:      |
|---|
| 25.0 degrees celsius single location          |
| Special Features:                             |
| Luminescent red band visible in trip position |
| Frequency In Hertz:                           |
| 400.0 single location                         |
| Thread Series Designator:                     |
| Unc   |
| Terminal Type And Quantity:                   |
| 2 screw                                       |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |

No Fiig: A030a0