NSN 5925-00-400-4938

Circuit Breaker - Page 1 of 2

Time delay all locations



View Online at https://aerobasegroup.com/nsn/5925-00-400-4938

| Body Length: |
|--|
| 2.500 inches |
| Body Width: |
| 1.500 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.938 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 0.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.062 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Fragility Factor: |
| Moderately rugged |
| Boss Height: |
| 0.140 inches |
| Mounting Surface To Terminal End Distance: |
| 2.611 inches |
| Pole Quantity: |
| 2 |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 5.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 250.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 1000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Magnetic-hydraulic all locations |
| Trip Release Characteristic: |

NSN 5925-00-400-4938 Circuit Breaker - Page 2 of 2



| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
|--|
| 150.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 2 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At each pole |
| External Actuator Linkage Arrangement: |
| One and two linked |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 4.000 at 200 pct all locations and 10.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| Fungus resistant |
| Frequency In Hertz: |
| 60.0 all locations |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 4 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |