## NSN 5925-00-401-6274

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-401-6274 **Body Style:** Single pole type **Body Length:** 2.300 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.680 inches **Boss Height:** 0.115 inches **Mounting Surface To Terminal End Distance:** 2.510 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 60.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

1 toggle

**Manual Actuator Type And Quantity:** 

## **NSN 5925-00-401-6274** Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.250 at 200 pct single location and 0.650 at 200 pct single location
Inclosure Protection Type For Which Designed:
Corrosion resistant and fungus resistant
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0