NSN 5925-00-402-3713

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-402-3713 **Body Style:** Single pole type **Overall Length:** 3.156 inches **Body Width:** 1.875 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.062 inches **Unthreaded Mounting Hole Diameter:** 0.257 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.406 inches **Mounting Surface To Terminal End Distance:** 1.125 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 120.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location **Ultimate Trip Time Per Pole In Seconds:** 150.000 single location **Reset Method:** Automatic

Internal Trip Release Configuration:

Series trip single location

NSN 5925-00-402-3713

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 200 pct single location and 1.500 at 300 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0