

View Online at <https://aerobasegroup.com/nsn/5925-00-405-1208>

Body Style:

Multipole-single actuator type

Body Length:

8.000 inches

Body Width:

4.500 inches

Body Height:

4.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Boss Height:

0.156 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations and 125.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

150.000 at 200 pct all locations and 250.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Special Features:

With bolt-on bracket connection

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 clip and 3 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0