NSN 5925-00-407-1738



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-407-1738 **Body Style:** Single pole type **Body Length:** 3.000 inches **Body Width:** 0.730 inches **Body Height:** 2.561 inches **Case Material: Plastic Boss Height:** 0.160 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

At pole one

Actuator Position Designation:

NSN 5925-00-407-1738

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 35.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 clip and 1 compression

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0