

View Online at <https://aerobasegroup.com/nsn/5925-00-411-0843>

Body Style:

Multipole-single actuator type

Body Length:

Between 3.960 inches and 4.000 inches

Body Width:

Between 2.220 inches and 2.270 inches

Body Height:

Between 2.360 inches and 2.400 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

Between 0.730 inches and 0.770 inches

Unthreaded Mounting Hole Diameter:

0.170 inches

Boss Height:

Between 0.220 inches and 0.260 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

0.008 at 200 pct all locations and 0.017 at 200 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0