# NSN 5925-00-412-4155

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-412-4155

#### **Body Style:**

Multipole-multiple actuator type

#### **Body Length:**

3.000 inches

### Body Width:

1.478 inches

#### **Body Height:**

2.312 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Width:

0.739 inches

#### **End Application:**

Nsn 4210-01-486-1035 tfft (tactical fire fighting truck)

#### **Boss Height:**

0.188 inches

## Pole Quantity:

2

#### Mounting Facility Type And Quantity:

2 clip

#### Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

70.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

2 toggle

# NSN 5925-00-412-4155

Circuit Breaker - Page 2 of 2

Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct all locations and 25.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 clip and 2 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0

