

View Online at <https://aerobasegroup.com/nsn/5925-00-427-9930>

Overall Length:

3.625 inches

Body Width:

1.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.316 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.125 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.328 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

7.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct single location and 100.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Shock resistant and explosion proof and sand resistant and vibration resistant and dusttight and corrosion resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0