

View Online at <https://aerobasegroup.com/nsn/5925-00-432-9116>

**Body Style:**

Single pole type

**Bushing Length:**

Between 0.381 inches and 0.401 inches

**Body Length:**

Between 1.803 inches and 1.823 inches

**Body Width:**

Between 0.553 inches and 0.573 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.146 inches and 1.166 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

Between 2.240 inches and 2.260 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

27

**Maximum Continuous Load Current Rating Per Pole:**

8.0 amperes ac single location and 8.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 24.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

80.0 ac single location and 80.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct single location and 40.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Waterproof and dustproof

**Frequency In Hertz:**

60.0 single location

**Unpackaged Unit Weight:**

1.000 ounces

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A030a0