## NSN 5925-00-434-1562

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-434-1562

**Body Style:** Multipole-single actuator type **Body Length:** 15.500 inches **Body Width:** 8.250 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 11.625 inches **Center To Center Distance Between Terminals Parallel To Width:** 2.750 inches **Unthreaded Mounting Hole Diameter:** 0.438 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 14.250 inches **Switch Contact Arrangement:** Single pole, single throw, normally open Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.750 inches **Boss Height:** 0.150 inches **Mounting Surface To Terminal End Distance:** 10.220 inches **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 700.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 416.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 20000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations

**Trip Release Method:**Thermal all locations

## **NSN 5925-00-434-1562** Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
4 alarm
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
135.0 degrees fahrenheit all locations
Switch Terminal Type:
Wire lead
Special Features:
Includes front mounted cover; includes 24 volt dc motor control unit complete with mounting hardware
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0